

## ADDRESSABLE RS232-RS485 INTERFACES

### Features

- > General purpose addressable interface
- > Allows any slave serial device that uses asynchronous serial communications (terminals, printers, barcode readers, etc.)
- > The host side of the interface is RS485/422
- > The slave side of the interface is either RS232 or RS485/422



AC31A Obsolete

### DESCRIPTION

The AC31 adapter card is a general purpose addressable interface that allows any slave serial device that uses asynchronous serial communications (terminals, printers, barcode readers, etc.) to be addressed and attached to a multidrop network. The host side of the interface is RS485/422.

The slave side of the interface is either RS232 or RS485/422.



AC31B - Obsolete

### SPECIFICATIONS

Power Requirements AC31A	115 VAC ± 10 VAC @ 60 Hz 220 VAC ± 20 VAC @ 50 Hz 10 - 28 VDC; 10 VDC @ 0.75 amps, 24 VDC @ 0.25 amps
Power Dissipation	Less than 4 watts @ 25° C
Operating Temperature Range	0° to 70° C 0 to 95% Humidity (non-condensing)
Interface Slave	Full duplex selectable RS232 & RS485/422 serial port
Interface Host	Full duplex RS-485/422 serial port
Baud Rate	300, 1200, 2400, 4800, 9600, 19200, and 38400 baud
CPU	64,180 8-bit microprocessor
CPU Clock Frequency	6.144 MHz
EPROM	32K bytes
RAM	32K bytes
Indicators	Transmit, receive, and power
Options Jumper Selectable	Address (0 to 255) Baud rates Terminating and biasing resistors
Agency Approvals	UL, CSA, CE; UKCA



AC31C - Obsolete


**\*\*\* NOTE: AC31A and AC31B are obsolete and no longer available when current stock is depleted. AC31C is obsolete and no longer available \*\*\***

*Please contact Opto 22 Pre-Sales engineers to discuss options for your*

### Part Number

Part	Description
AC31A [Obsolete]	Addressable RS232 Interface 120 VAC
AC31B [Obsolete]	Addressable RS485 Interface 220 VAC
AC31C [Obsolete]	Addressable RS232 Interface DC

## DIMENSIONS



## PRODUCTS

Opto 22 develops and manufactures reliable, easy-to-use, open standards-based hardware and software products. Industrial automation, process control, remote monitoring, data acquisition, and industrial internet of things (IIoT) applications worldwide all rely on Opto 22.

### groov RIO®

*groov RIO edge I/O* offers a single, compact, PoE-powered industrial package with web-based configuration and IIoT software built in, support for multiple OT and IT protocols, and security features like a device firewall, data encryption, and user account control.

Standing alone, *groov RIO* connects to sensors, equipment, and legacy systems, collecting and securely publishing data from field to cloud. Choose a universal I/O model with thousands of possible field I/O configurations, with or without Ignition from Inductive Automation®, or a *RIO EMU energy monitoring unit* that reports 64 energy data values from 3-phase loads up to 600 VAC, Delta or Wye.

You can also use *groov RIO* with a Modbus/TCP master or as remote I/O for a *groov EPIC* system.

### groov EPIC® System

Opto 22's *groov Edge Programmable Industrial Controller (EPIC) system* gives you industrially hardened control with a flexible Linux®-based processor with gateway functions, guaranteed-for-life I/O, and software for your automation and IIoT applications.

### groov EPIC Processor

The heart of the system is the *groov EPIC* processor. It handles a wide range of digital, analog, and serial functions for data collection, remote monitoring, process control, and discrete and hybrid manufacturing.

In addition, the EPIC provides secure data communications among physical assets, control systems, software applications, and online services, both on premises and in the cloud. No industrial PC needed.

Configuring and troubleshooting I/O and networking is easier with the EPIC's integrated high-resolution color touchscreen. Authorized users can manage the system locally on the touchscreen, on a monitor connected via the HDMI or USB ports, or on a PC or mobile device with a web browser.

### groov EPIC I/O

*groov I/O* connects locally to sensors and equipment. Modules have a spring-clamp terminal strip, integrated wireway, swing-away cover, and LEDs indicating module health and discrete channel status. *groov I/O* is hot swappable, UL Hazardous Locations approved, and ATEX compliant.

### groov EPIC Software

The *groov EPIC* processor comes ready to run the software you need:

- Programming: Choose flowchart-based PAC Control, CODESYS Development System for IEC61131-3 compliant programs, or secure shell access (SSH) to the Linux OS for custom applications
- Node-RED for creating simple IIoT logic flows from pre-built nodes
- Efficient MQTT data communications with string or Sparkplug data formats
- Multiple OPC UA server options
- HMI: *groov View* to build your own HMI viewable on touchscreen, PCs, and mobile devices; PAC Display for a

Windows HMI; Node-RED dashboard UI

- Ignition or Ignition Edge® from Inductive Automation (requires license purchase) with OPC-UA drivers to Allen-Bradley®, Siemens®, and other control systems, and MQTT communications

### Older products

From solid state relays, to world-famous G4 and SNAP I/O, to SNAP PAC controllers, older Opto 22 products are still supported and working hard at thousands of installations worldwide. You can count on us for the reliability and service you expect, now and in the future.

## QUALITY

Founded in 1974, Opto 22 has established a worldwide reputation for high-quality products. All are made in the U.S.A. at our manufacturing facility in Temecula, California.

Because we test each product twice before it leaves our factory rather than testing a sample of each batch, we can afford to guarantee most solid-state relays and optically isolated I/O modules for life.

## FREE PRODUCT SUPPORT

Opto 22's California-based Product Support Group offers free technical support for Opto 22 products from engineers with decades of training and experience. Support is available in English and Spanish by phone or email, Monday–Friday, 7 a.m. to 5 p.m. PST.

Support is always available on our website, including [free online training](#) at OptoU, how-to [videos](#), [user's guides](#), the Opto 22 KnowledgeBase, and [OptoForums](#).

## PURCHASING OPTO 22 PRODUCTS

Opto 22 products are sold directly and through a worldwide network of distributors, partners, and system integrators. For more information, contact Opto 22 headquarters at **800-321-6786** (toll-free in the U.S. and Canada) or **+1-951-695-3000**, or visit our website at [www.opto22.com](http://www.opto22.com).

