

HIGH-SPEED ISA BUS TO REMOTE BUS ADAPTER CARD

Features

- > Isolated, high-speed serial interface for AT-class IBM-compatible computers
- > Compatible with all Opto 22 16-bit and 32-bit software and hardware

DESCRIPTION

The AC37 is an isolated, high-speed serial interface for AT-class IBM-compatible computers. Reliable half- and full-duplex RS-485 communication is provided through a single or dual twisted-pair cable. Hardware interrupts on the Mystic remote bus are implemented by using a second twisted-pair.

Buffering on the card prevents loss of data and provides optical and transformer isolation and transient protection to the RS-485 communication lines. AC 37 is compatible with all Opto 22 16-bit and 32-bit software and hardware.

This product is obsolete and no longer available.

SPECIFICATIONS

Power requirements	5 VDC @ 800 mA
Operating Temperature	0° C to 60° C
Relative Humidity	95% relative humidity, non-condensing
Isolation	2,500 VAC transient
Baud rates	Serial link to 460,800 baud
Cable length distance	Up to 3,000 ft. @ 115,200 baud
Communications	RS-485 2-wire half-duplex or 4-wire full-duplex operation
Agency Approvals	UL, CE; UKCA



AC37 [Obsolete]


Part Numbers

Part	Description
AC37 [Obsolete]	ISA Bus High-Speed Serial Co-Processor, RS485 [Obsolete]

COMMUNICATIONS

A G4 remote I/O bus will always use one twisted-pair cable for communication. A second pair can optionally be used in systems needing the G4 interrupt capability. All wiring must be terminated at both ends of the cable. In most cases, the AC37 will be one of the ends. An additional wire should be used as a common reference to eliminate potential common mode voltage problems. A grounded shield should also be used in electrically noisy environments.

TYPICAL CONNECTION USING SNAP B3000



PRODUCTS

Opto 22 develops and manufactures reliable, easy-to-use, open standards-based hardware and software products. Industrial automation, process control, remote monitoring, data acquisition, and industrial internet of things (IIoT) applications worldwide all rely on Opto 22.

groov RIO®

groov RIO edge I/O offers a single, compact, PoE-powered industrial package with web-based configuration and IIoT software built in, support for multiple OT and IT protocols, and security features like a device firewall, data encryption, and user account control.

Standing alone, groov RIO connects to sensors, equipment, and legacy systems, collecting and securely publishing data from field to cloud. Choose a universal I/O model with thousands of possible field I/O configurations, with or without Ignition from Inductive Automation®, or a RIO EMU energy monitoring unit that reports 64 energy data values from 3-phase loads up to 600 VAC, Delta or Wye.

You can also use groov RIO with a Modbus/TCP master or as remote I/O for a groov EPIC system.

groov EPIC® System

Opto 22's groov Edge Programmable Industrial Controller (EPIC) system gives you industrially hardened control with a flexible Linux®-based processor with gateway functions, guaranteed-for-life I/O, and software for your automation and IIoT applications.

groov EPIC Processor

The heart of the system is the groov EPIC processor. It handles a wide range of digital, analog, and serial functions for data collection, remote monitoring, process control, and discrete and hybrid manufacturing.

In addition, the EPIC provides secure data communications among physical assets, control systems, software applications, and online services, both on premises and in the cloud. No industrial PC needed.

Configuring and troubleshooting I/O and networking is easier with the EPIC's integrated high-resolution color touchscreen. Authorized users can manage the system locally on the touchscreen, on a monitor connected via the HDMI or USB ports, or on a PC or mobile device with a web browser.

groov EPIC I/O

groov I/O connects locally to sensors and equipment. Modules have a spring-clamp terminal strip, integrated wireway, swing-away cover, and LEDs indicating module health and discrete channel status. groov I/O is hot swappable, UL Hazardous Locations approved, and ATEX compliant.

groov EPIC Software

The groov EPIC processor comes ready to run the software you need:

- Programming: Choose flowchart-based PAC Control, CODESYS Development System for IEC61131-3 compliant programs, or secure shell access (SSH) to the Linux OS for custom applications
- Node-RED for creating simple IIoT logic flows from pre-built nodes
- Efficient MQTT data communications with string or Sparkplug data formats
- Multiple OPC UA server options
- HMI: groov View to build your own HMI viewable on touchscreen, PCs, and mobile devices; PAC Display for a

Windows HMI; Node-RED dashboard UI

- Ignition or Ignition Edge® from Inductive Automation (requires license purchase) with OPC-UA drivers to Allen-Bradley®, Siemens®, and other control systems, and MQTT communications

Older products

From solid state relays, to world-famous G4 and SNAP I/O, to SNAP PAC controllers, older Opto 22 products are still supported and working hard at thousands of installations worldwide. You can count on us for the reliability and service you expect, now and in the future.

QUALITY

Founded in 1974, Opto 22 has established a worldwide reputation for high-quality products. All are made in the U.S.A. at our manufacturing facility in Temecula, California.

Because we test each product twice before it leaves our factory rather than testing a sample of each batch, we can afford to guarantee most solid-state relays and optically isolated I/O modules for life.

FREE PRODUCT SUPPORT

Opto 22's California-based Product Support Group offers free technical support for Opto 22 products from engineers with decades of training and experience. Support is available in English and Spanish by phone or email, Monday–Friday, 7 a.m. to 5 p.m. PST.

Support is always available on our website, including [free online training](#) at OptoU, how-to [videos](#), [user's guides](#), the Opto 22 KnowledgeBase, and [OptoForums](#).

PURCHASING OPTO 22 PRODUCTS

Opto 22 products are sold directly and through a worldwide network of distributors, partners, and system integrators. For more information, contact Opto 22 headquarters at **800-321-6786** (toll-free in the U.S. and Canada) or **+1-951-695-3000**, or visit our website at www.opto22.com.

